

型号参数/Model		单位/Unit	PET-L2MJ	PET-L5MJ
主机参数 Clamping System	腔数 Cavity Quantity	Cavities	2	4
	锁模力Clamping Force	Kg	35000	48000
	开模行程 Mould Opening Stroke	Mm	125	125
	拉伸杆行程 Stretching Rod Stroke	Mm	360	360
	底模行程 Bottom Mould Stroke	Mm	50	50
	瓶胚间距 Pitch Distane	Mm	114.3	114.3
	胚头数 Number of Preform Holder	Pcs	50	72
	制品参数 Container Spec.	最大容量 Max. Container Volume	L	2
最大瓶身高度 Max. Container Height		Mm	350	350
最大瓶身直径 Max. Container Diameter		Mm	100	100
最大瓶胚高度 Max. Preform Height		Mm	160	160
最大瓶口外径 Max. Neck Diameter		Mm	85	85
产量/Output		BPH	1600-7000	3000-3200
电气参数 Electrical System	加热炉数量 Heating oven quantity	Zone	4x4	4x4
	灯管数量 Number of Lamp	Pcs	4x10	4x10
	加热配置功率 Heating Power	Kw	60	80
	电力总容量 Installed Powet	Kw	65	85
	电压 Voltage		Customized	Customized
	实际功率 Actual Power	Kw	15-20	15-20
	气源参数 Air System	工作压力 Operating Power	Mpa	0.7-0.9
吹瓶压力 Blowing Pressure		Mpa	2.5-3.0	2.5-3.0
高压耗气量 High Pressure Air Consumption		Umin	4.0/40	6.0/40
冷却水参数 Chiller System	温度范围 Temperature Range	Degree	9-13	9-13
	压力 Pressure	Mpa	0.4	0.4
	容量 Capacity	Hp	3	5
外形尺寸 Machine	主机尺寸 Machine Dimension	M	3.1x1.7x2.2	3.6x2.2x2.2
	重量 Machine Weight	Kg	3500	4500