

型号参数/Model		单位/Unit	PET-L2MS	PET-L3MS	PET-L4S	PET-L4MS	PET-L6S	PET-L6MS	PET-L9S	
主机参数 Clamping System	腔数 Cavity Quantity	Cavity	2	3	4	4	6	6	6	
	锁模力Clamping Force	Kg	3000	3500	4000	5600	6500	7500	6500	
	开模行程 Mould Opening Stroke	Mm	90	125	90	125	60	125	90	
	拉伸杆行程 Stretching Rod Stroke	Mm	350	350	260	350	260	350	260	
	拉伸杆直径 Stretching Rod Dia	Mm	12	12	10	12	10	12	10	
	底模行程 Bottom Mould Stroke	Mm	50	50	50	50	50	50	50	
	瓶胚间距 Pitch Distane	Mm	114.3	114.3	76.2	114.3	76.2	114.3	76.2	
	瓶胚架数量 Preform Holder Quantity	Pcs	58	72	92	88	126	120	180	
制品参数 Container Spec.	最大容量 Max. Container Volume	MI	2000	2000	600	2000	600	2000	600	
	最大瓶身高度 Max. Container Height	Mm	350	350	260	350	260	350	260	
	最大瓶身直径 Max. Container Diameter	Mm	100	100	70	100	70	100	70	
	最大瓶胚高度 Max. Preform Height	Mm	100	140	100	140	100	140	100	
	最大瓶口外径 Max. Neck Diameter	Mm	38	38	38	38	38	38	38	
600毫升的生产率 Productivity for 600ml	BPH	3000-3600	4000-4200	4800-5200	4800-5200	7000-8000	7000-8000	12000-13000		
1500毫升的生产率 Productivity for 1500ml	BPH	2000-2200	3400-3600		4000-4200		5500-6000			
电气参数 Electrical System	加热炉数量 Heating oven quantity	Zone	2	4	4	5	6	10	10	
	灯管数量 Number of Lamp	Pcs	2*10	4*10	4*6	5*10	6*6	10*10	6*10	
	加热配置功率 Heating Power	Kw	30	60	36	75	54	150	90	
	电力总容量 Installed Powet	Kw	36	66	42	82	62	162	102	
	电压Voltage		380V,3 phase, 50Hz							
	实际功率 Actual Power	Kw	15-20	30-35	20-25	35-40	25-30	70-80	45-50	
气源参数 Air System	工作压力 Operating Power	Mpa	0.7-0.9	0.7-0.9	0.7-0.9	0.7-0.9	0.7-0.9	0.7-0.9	0.7-0.9	
	吹瓶压力 Blowing Pressure	Mpa	2.5-3.0	2.5-3.0	2.5-3.0	2.5-3.0	2.5-3.0	2.5-3.0	2.5-3.0	
	高压耗气量 High Pressure Air Consum.	Umin	2.4/30	3.6/30	3.6/30	4.8/30	6.0/30	7.2/30	10.0/40	
冷却水参数 Chiller System	温度范围 Temperature Range	Degree	9-13	9-13	9-13	9-13	9-13	9-13	9-13	
	压力 Pressure	Mpa	0.4	0.4	0.4	0.4	0.4	0.4	0.4	
	容量 Capacity	Hp	5	5	5	5	10	10	10	
外形尺寸 Machine	主机尺寸 Machine Dimension	M	3.2x1.7x2.08	3.45x2x2.04	3.76*1.7*2.08	4.8x2.05x2.08	4.5*1.9*2.08	6.4x2.12x2.08	6.4x2.1x2.08	
	重量 Machine Weight	Kg	3000	3500	3500	3500	6000	7000	7000	