

型号参数/Model	单位/Unit	PET-B3L	PET-B5L	PET-B5L2	PET-B10L
最大制品容积 Max. Volume of Product	L	3 (2-cavity)	5 (1-cavity)	5(2-cavity)	10(1-cavity)
产量 Output	BPH	800-1200	300-600	500-1200	300-400
制品瓶口尺寸 Neck Size of Product	Mm	≤70	≤70	≤70	≤70
有效模具尺寸 Useful Area of Mould	Mm	360x410	345x470	480X500	345x470
模厚 Mould thickness	Mm	90-220	110-280	160-330	160-330
开模行程 Mould Opening Stroke	Mm	155	230	350	265
锁模力 Clamping Force	Kn	8T	10T	10T	10T
工作压力 Working Pressure	Kpa	≤4.0	≤4.0	≤4.0	≤4.0
主机耗电 Power of Main Blower	Kw	0.2	0.2	0.2	0.2
主机重量 Weight of Main Blower	Kg	800	700	800	700
主机尺寸 Dimension of Main Blower	mm	1520x580x1780	1960x642x1700	2120x790x1710	1960x642x1700
烘箱耗电 Power of Preheater	Kw	12	10	10	10
烘箱重量 Weight of Preheater	Kg	450	300	300	300
烘箱尺寸 Dimension of Preheater	Mm	1450x700x1150	2170x585x1360	2170x585x1360	2170x585x1360